

BOS CHAMPION 6500 BHP | 85 TBP | DP2

Class Notation: LR 100A1 AHTS, Fire-Fighting Ship 1 (2,400 m3/h) with Water Spray, HNLS, Oil Recovery, *IWS, WDL (7t/m2 from Aft to Frame 70), ECO(TOC)
LMC, UMS, DP(AA)
ShipRight (IHM-EU+)

Main Particulars

Flag: Singapore Call Sign 9V3690 IMO No. 9749635 Year Built 2016 Design Draft 5.4m Max Summer Draft 5.8m Gross Tonnage 2,387 T 716 T Net Tonnage Deadweight (Max Draught) 1,781 T Displacement 4,001 T

Dimensions

Length Overall 65m Beal Overall 16.4m Depth Moulded 6.8m

Performance

Fuel consumption at 9.5 knots Abt 12 m³/day
Fuel consumption at 7.5 knots Abt 8.3 m³/day
Towing at 4.5 knots Abt 17 m³/day
DP mode Abt 5 m³ to 7 m³/day
General field duties - average Abt 7 m³/day

*Subject to actual weather and operating conditions

Cargo Deck

 Deck Cargo Area
 425m²

 Deck Cargo Dimension
 31.5m x 13.5m

 Deck Cargo Capacity
 700T

 Deck Strength
 7T/m²

Capacities

Cargo Fuel Oil Tank* 557 m³
Fresh Water 414 m³
Drill Water* 1,200 m³
Liquid mud / brine / ORO* 395 m³
Dry Bulk Tank 186 m³
Foam 12m³
Detergent 12 m³
*Indicates tanks with shared capacity

Main Engines & Generators

Main Engine 2 x MAK 8M25C 2,400 kW Generator 3 x 450 kW diesel driven

Thrusters & Propulsion

Bow Thruster 2 x 8 t (550 kW) electric driven
Stern Thruster 8 t (550 kW) electric driven
Propeller CPP

Deck Crane

Fixed Crane 3T SWL @ 10m

Anchor Handling/Tow Equipment

Tow/Anchor Handling Winch
Stall Pull Capacity

Brake Holding Capacity

MacGregor
150T
250T

Tow Drum Capacity

Anchor Handling Capacity

Spare tow wire capacity

Tugger Winch

Capstan

Capstan

Tow Pins

1,500 m x 64 mm wire rope

2 x 10T @ 15m/min

2 x ST @ 15m/min

2 x ST @ 15m/min

2 x ST WL

2 x 300T SWL

5m x 1.6m; 300T

Mooring Equipment

Stern Roller

 Anchor
 2 x 1,610 kg

 Anchor Chain
 2 x 440m x 40mm

 Anchor Windlass
 MacGregor

Dynamic Positioning System

DP Class Class 2

References 2 x DGPS; 1 x Laser (Cyscan MK4)

Joystick Kongsberg C_Joy

Discharge Rates

 Drill Water/Pump
 100 m³/hr @ 70m head

 Fresh Water/pump
 100 m³/hr @ 70m head

 Fuel/Pump
 100 m³/hr @ 70m head

 Liquid Mud/Brine/ORO
 75 m³/hr @ 70m head

 Dry Bulk Tank
 40 m³/hr @ 60m head

Comminications Equipment HF radio Fu Furuno model RC-1800T VHF radio Furuno FM-8800S

Portable VHF radio 3 x McMurdo Model R2 GMDSS Satellite EPIRB McMurdo model SMARTFIND E5 Navtex receiver Furuno NX-700A (GMDSS) SART 2 x McMurdo S4 Rescue SART

AIS Furuno FA-150

Remote Fuel Monitoring System Krohne flow meters + eGenKit system

Navigation Equipment Radar no. 1 X-Band radar Radar no. 2 S-Band radar GPS **GPS** plotter

Echo sounder Navigational Echo-Sounder

ElectronicChartDisplaySystem **ECDIS**

Auto pilot Auto pilot system 3 x gyro compass Gyro compass Magnetic compass 1 x magnetic compass Dynamic positioning Kongsberg DPS-2

Fire Fighting and Rescue

FiFi Pump 2 x 1,200 m³/hr FiFi Monitor 2 x 1,200 m³/hr Spray Boom 2 x 6m

Rescue Boat 1 x 6 men with 25hp OBM

Accommodation

Cabins 11 x 1 bed; 14 x 2 beds Total 39 beds

1 bed Hospital

